



Flex Hoses

Complete flexible sprinkler hose assembly for fast and easy installation



...and NOW with



CE-approved flex hoses, available in multiple sizes, with a wide range of approved accessories for easy installation.

Flex hoses are designed to allow the easier and faster installation of sprinklers in a variety of situations. They are now CE-marked ensuring European compliance in addition to all major fire protection approvals from UL, FM, VdS and LPCB. Available in a range of sizes and with many accessories, they offer flexibility and proven performance for sprinkler systems.

Key advantages:

- **Fast and effortless installation:** Suitable for pendent, recessed, sidewall and concealed sprinklers
- **Easy to use fittings:** designed for efficient and simple on-site installation
- **Multiple hose lengths:** available to suit different installations and applications
- **Multiple diameters:** suitable for sprinklers up to K360
- **Standard support bar:** 700 mm bar fits most ceiling grids (longer versions available on request)
- **Cold storage:** special bracket for dry sprinkler (OD33.4mm)
- **Flexible routing:** Multiple bends allowed
- **Low equivalent length values**
- **Aid in positioning:** Outlet fitting marked with distance from outlet to support accurate positioning
- **S-Flex option:** High-performance hose designed for easy bending in false ceiling installations and improved hydraulic performance.

SPECIFICATIONS

Models:	VK25B, VK27B, VK27SB, VK29B, VK32SB & VK40SB
Material:	Stainless steel
Accessory materials:	Carbon, Steel, Nitrile rubber, Stainless Steel
Finish:	Braided & unbraided
Lengths (mm):	700, 1,000, 1,200, 1,500 & 1,800
Maximum ambient temperature:	100 °C (212 °F)
Various diameters:	25, 27, 29, 32 and 40 mm

For more information, please contact your local Viking sales office or refer to the technical documentation.

The contents of this publication are subject to modifications without notice.

Trusted above all.

